

STATE-SPACE MODELING

Topics Covered

- Modeling from first-principles.
- State-space representation.
- Model validation.

Prerequisites

- Hardware Interfacing laboratory experiment.
- Filtering laboratory experiment.

1 Background

1.1 Linear State-Space Representation

The standard state-space representation of a multi-input multi-output (MIMO) continuous linear-time invariant (LTI) system with n state variables, r input variables, and m output variables is

$$\dot{x}(t) = Ax + Bu \quad (1.1)$$

$$y(t) = Cx(t) + Du(t) \quad (1.2)$$

where x is the vector of state variables ($n \times 1$), u is the control input vector ($r \times 1$), y is the output vector ($m \times 1$), A is the system matrix ($n \times n$), B is the input matrix ($n \times r$), C is the output matrix ($m \times n$), and D is the feed-forward matrix ($m \times r$).

The block diagram representation of state-space Equation 1.1 and Equation 1.2 is shown in Figure Figure 1.1.




Figure 1.1: State-Space Block Diagram

1.2 DC Motor Modeling

This section summarizes how to find the equations of motion (EOMs) of the DC motor. The motor electrical equation is

$$v_m(t) - R_m i_m(t) - k_m \dot{\theta}_m(t) = 0 \quad (1.3)$$

where $v_m(t)$ is the motor input voltage (the control input), R_m is the motor electrical resistance, $i_m(t)$ is the current, k_m is the back-emf constant, and $\theta_m(t)$ is the angular position of the motor shaft (i.e. the inertia disc).

The motor shaft equation is expressed as

$$J_{eq} \ddot{\theta}(t) = \tau_m(t) \quad (1.4)$$

where J_{eq} is the total or equivalent moment of inertia acting on the motor shaft and τ_m is the applied torque from the DC motor. Based on the current applied, the torque is

$$\tau_m(t) = k_t i_m(t) \quad (1.5)$$

where k_t is the motor current torque constant.

See Block Diagram Modeling laboratory experiment for more information about finding the servo equations of motion.

2 In-Lab Exercises

The **SIMULINK**[®] model shown in Figure 2.1 applies a 1 V step to the QUBE-Servo 2 hardware, using **QUARC**[®], and the state-space model of the servo. The measured and simulated speed response (i.e. from the model) are plotted in the same scope to compare.






Figure 2.1: Applies a step voltage and displays measured and simulated DC motor response.

1. Formulate the differential equation relating the motor position, θ_m , and the motor input voltage, $v_m(t)$, using Equation 1.3, Equation 1.4, and Equation 1.5.
2. Derive the state-space model of the DC motor from the differential equation you obtained in Exercise 1 for the following state variables: $x_1 = \theta_m(t)$ and $x_2 = \dot{\theta}_m(t)$, $y_1 = \theta_m(t)$ and $y_2 = \dot{\theta}_m(t)$ (i.e. measuring motor position and speed), and the input variable $u = v_m(t)$.
3. Based on the state space model derived in Step 2 and using the parameters defined in the the **MATLAB**[®] script `qube2_param.m` provided, create the **MATLAB**[®] script that constructs a MATLAB state-space model and generate its step response.
4. Open or design the Simulink model shown in Figure 2.1. This applies a 1 V step to the QUBE-Servo 2 system and its state-space model. Use the model already designed in the Filtering laboratory experiment if Figure 2.1 is to be designed.
5. Run the **MATLAB**[®] script created in Exercise 3 to load the state space model parameters in the **MATLAB**[®] workspace. Ensure that the generated matrices match your solution in Step 2.
6. Build and run the model. The scope response should be similar to Figure 2.2. Attach a screen capture of your scopes. Does your model represent the actual DC motor well?



(a) Input Voltage (V)



(b) Motor Angular Rate (rad/s)

Figure 2.2: Step response of the DC motor and State-Space Model

7. Stop the **QUARC**[®] controller.

© 2021 Quanser Inc., All rights reserved.

Quanser Inc.
119 Spy Court
Markham, Ontario
L3R 5H6
Canada
info@quanser.com
Phone: 1-905-940-3575
Fax: 1-905-940-3576

Printed in Markham, Ontario.

For more information on the solutions Quanser Inc. offers, please visit the web site at:
<http://www.quanser.com>

This document and the software described in it are provided subject to a license agreement. Neither the software nor this document may be used or copied except as specified under the terms of that license agreement. Quanser Inc. grants the following rights: a) The right to reproduce the work, to incorporate the work into one or more collections, and to reproduce the work as incorporated in the collections, b) to create and reproduce adaptations provided reasonable steps are taken to clearly identify the changes that were made to the original work, c) to distribute and publically perform the work including as incorporated in collections, and d) to distribute and publicly perform adaptations. The above rights may be exercised in all media and formats whether now known or hereafter devised. These rights are granted subject to and limited by the following restrictions: a) You may not exercise any of the rights granted to You in above in any manner that is primarily intended for or directed toward commercial advantage or private monetary compensation, and b) You must keep intact all copyright notices for the Work and provide the name Quanser Inc. for attribution. These restrictions may not be waved without express prior written permission of Quanser Inc.