

# SERVO MOTOR

## Topics Covered

- Hobby Servos for position control.

## Prerequisites

- The QNET Mechatronic Actuators has been setup and tested. See the QNET Mechatronic Actuators Quick Start Guide for details.
- You have access to the QNET Mechatronic Actuators User Manual.
- You are familiar with the basics of [LabVIEW™](#).

# 1 Background

A servomechanism is a device that uses a feedback sensor to automatically adjust the behaviour of a system using feedback control. A DC servo motor, or servo, is a rotary actuator that transforms electrical energy into mechanical energy incorporating a feedback mechanism for position control. It holds the commanded position, even under load, until it is instructed to do otherwise.

A typical servo includes a motor, a gearbox, a potentiometer to sense angular position, and a control circuit. The gearbox is used to generate a high holding torque compared to standalone motors of a similar size. The travel range of servos is typically restricted to be  $\pm 180^\circ$ , with the position command provided as a pulse width modulation (PWM) signal. Whenever the servo is pulsed with a low pulse width, also called *Minimum Pulse*, the motor will remain in the low position. A neutral pulse will result in a rotation of half the range, and a large pulse, also referred to as *Maximum Pulse*, will result in a rotation to the full range of the servo, see Figure 1.1. Note that the pulse length that is required to command a certain position varies between servos. In the case of the servo used on the QNET Mechatronic Actuators, the servo is provided with a 3-5V pulse, at 50Hz. The width of the pulse is varied between 0.9ms and 2.1ms, with a pulse width of 1.5ms corresponding to the neutral (centre) position.




Figure 1.1: Commanding the servo position

## 2 In-Lab Exercise

1. Open the QNET Actuators - Servo Motor.vi. **Make sure the correct Device is chosen.**
2. Run the VI, and enable the servo using the Servo Enable, button.
3. Vary the Servo Pulse Width between 0.9 and 2.1 ms. Measure the resultant servo angles on the cog wheel using a protractor, or other angle measurement device.
4. Based on your measurements, determine a calibration gain to allow you to command the servo using a desired angle command in degrees.
5. Enter your calculated calibration gain into the field on the front panel, and ensure that the Command Type is set to *Position*. Vary the commanded position, and verify that your gain is correct.
6. Using either the position or pulse width command fields, command the servo motor to traverse its full range and record the resultant speed and current profile.
7. Analyze the response and comment on the current control profile. Try moving the servo through a series of positions by sweeping the command dial back and forth. How does the measured current relate to the position of the servo?  
**Note:** Think about the elements of the servo motor and how it achieves the desired position.
8. Click on the Stop button to stop the VI.

© 2015 Quanser Inc., All rights reserved.

Quanser Inc.  
119 Spy Court  
Markham, Ontario  
L3R 5H6  
Canada  
info@quanser.com  
Phone: 1-905-940-3575  
Fax: 1-905-940-3576

Printed in Markham, Ontario.

For more information on the solutions Quanser Inc. offers, please visit the web site at:  
<http://www.quanser.com>

This document and the software described in it are provided subject to a license agreement. Neither the software nor this document may be used or copied except as specified under the terms of that license agreement. Quanser Inc. grants the following rights: a) The right to reproduce the work, to incorporate the work into one or more collections, and to reproduce the work as incorporated in the collections, b) to create and reproduce adaptations provided reasonable steps are taken to clearly identify the changes that were made to the original work, c) to distribute and publically perform the work including as incorporated in collections, and d) to distribute and publicly perform adaptations. The above rights may be exercised in all media and formats whether now known or hereafter devised. These rights are granted subject to and limited by the following restrictions: a) You may not exercise any of the rights granted to You in above in any manner that is primarily intended for or directed toward commercial advantage or private monetary compensation, and b) You must keep intact all copyright notices for the Work and provide the name Quanser Inc. for attribution. These restrictions may not be waved without express prior written permission of Quanser Inc.