



深圳市驰海电机有限公司  
Chi Hai Motor(shenzhen)Co.,Ltd

## 客户产品规格书

## CUSTOMER SPECIFICATION

客户名称/Customer:

产品名称/Item: 直流铁芯驱动编码行星减速电机/DC Core Driving planet Gear Motor

产品型号/Model: CHP-42GP-775-5-ABHL 12V 820rpm 客户料号:

规格书编号/ SPECIFICATION NO: CL-20210105-01

版本/REVISION NO.: A/1.3

页码/Page:1/7

日期/DATE: 2022 年 07 月 27 日

我司确认:

Our Confirmed

| 批准<br>APPROVAL | 审核<br>CHECK | 制作<br>DESIGN |
|----------------|-------------|--------------|
| 郭仕海            | 黄辉明         | 曾键东          |
| 2022/ 07/27    | 2022/ 07/27 | 2022/ 07/27  |

确 认:  
Confirmed by

核 准:  
Approved by



|   |                      |                          |
|---|----------------------|--------------------------|
| 型号/MODEL<br>CHP-42GP-775-5-ABHL 12V<br>820rpm | 规格书<br>SPECIFICATION | 页码/PAGE: 2/7             |
|   |                      | 版本/REVISION NO.:A/1.3    |
|   |                      | 编号/SERIAL NO.: CL-QR-323 |

变更记录/REVISION RECORD

| 版本<br>REV.NO. | 更改原因<br>REVISION DESCRIPTION | 制作<br>DESIGN | 批准<br>APPROVAL | 日期<br>DATE |
|---------------|------------------------------|--------------|----------------|------------|
|               |                              |              |                |            |
|               |                              |              |                |            |
|               |                              |              |                |            |
|               |                              |              |                |            |
|               |                              |              |                |            |
|               |                              |              |                |            |

CAUTIONS:注意事项



- 1) Please use the motor in this technology index range for the performance of the motor is affected by environmental temperature seriously.  
环境温度条件对马达表现有极大影响，请在本技术指标范围内使用马达.
- 2) It is not allowed to operate in the high temperature with high humidity, and not allowed to contact with corrosive liquid and corrosive gas, should not to be stored and without running Continuously for more than six months.  
避免在高温，高湿，及与腐蚀性液体、气体接触.，连续存放不应超过 6 个月
- 3) Do not lock the motor shaft while the electric is on. The motor will be burnt out after the motor shaft was locked for more then 1 minute.  
请不要在马达运行时锁定电机轴.若持续锁定超过 1 分钟，马达将发热甚至烧毁.
- 4) Do not hit the motor directly.  
尽量避免直接碰撞马达.
- 5) Please ensure that the motor can satisfy the requirements of your application.  
请确保马达能满足贵司产品要求.

|   |                             |                          |
|---|-----------------------------|--------------------------|
| 型号/MODEL<br><b>CHP-42GP-775-5-ABHL 12V<br/>820rpm</b> | 规格书<br><b>SPECIFICATION</b> | 页码/PAGE: 3/7             |
|   |                             | 版本/REVISION NO.:A/1.3    |
|   |                             | 编号/SERIAL NO.: CL-QR-323 |

# 1、CHARACTERISTICS 特性参数

The test is made in principle of a temperature between 10℃ and 30℃,and at relative humidity between 30% and 95%.If the test result is questionable,it shall be judged from the test made at20℃±2℃、65%±5%RH and initial stage after 30 seconds run-in.

测试环境温度（10℃-30℃）、相对湿度 30%~95%；如对测试结果有疑问，可在温度 20℃±2℃、湿度 65%±5%的条件下和电机初始运转 30 秒钟后再做判定。

| NO.  | Items/项目                              | TEST CONDITIONS 测试条件  | Specifcation/规格            |
|------|---------------------------------------|---|----------------------------|
| 1-1  | Rated voltage<br>额定电压                 | (12.0) V DC   |                            |
| 1-2  | No load current<br>空载电流               | Rated voltage and no load<br>额定电压、无负载   | ≤ (700) mA                 |
| 1-3  | No load speed<br>空载转速                 | Rated voltage and no load<br>额定电压、无负载   | (820) rpm<br>±12%          |
| 1-4  | No load starting<br>voltage<br>空载起动电压 | NO load<br>无负载  | ≤ ( 5.0) V                 |
| 1-5  | Holzer signal<br>霍尔信号线数               | MOTOR 1r/min<br>电机每转一圈  | 17 PPR*5                   |
| 1-6  | Stall Current<br>堵转电流                 | At rated voltage(must be stable)<br>额定电压（马达两端电压必须保持稳定 12.0V）  | ≤ (13.0) A                 |
| 1-7  | Insulation Resistance<br>绝缘电阻         | Measured between motor terminal and motor<br>metal housing with 100VDC megameter 使用<br>DC 100 V 兆欧表，测量电机接线端子与机壳<br>之间的电阻  | ≥ (1.0) MΩ                 |
| 1-8  | Load characteristics<br>负载特性          | Load Torque 7.0 Kg.cm   | 410 rpm±12%<br>≤ (4.0) A   |
| 1-9  | Mechanical Noise<br>机械杂音              | Rated voltage and no load<br>operation.Background noise: ≤ 35 dB<br>额定电压、空载，环境噪音: ≤ 35 dB<br> | ≤ (58) dB                  |
| 1-10 | Current waveform<br>电流波形              | Rated voltage and no load<br>额定电压、无负载   | Free from off point<br>无死点 |
| 1-11 | Maximum axial load<br>最大轴向受力          | Direction of static load and support of load as<br>shown below<br>支撑点及受力如下图所示:<br>            |                            |

1[g.cm]=0.098[mN.m], 1[mN.m]=10.197[g.cm]


|   |                      |                          |
|---|----------------------|--------------------------|
| 型号/MODEL<br>CHP-42GP-775-5-ABHL 12V<br>820rpm | 规格书<br>SPECIFICATION | 页码/PAGE: 4/7             |
|   |                      | 版本/REVISION NO.: A/1.3   |
|   |                      | 编号/SERIAL NO.: CL-QR-323 |

2、Encoder parameter data 编码器参数资料

| NO.  | Items 项目                        | Specifcation/规格     |
|------|---------------------------------|---------------------|
| 2-1  | Application<br>用途               | DC Motor            |
| 2-2  | Speed fbk sel<br>编码器类型          | AB 双相磁性霍尔编码器        |
| 2-3  | Rated Voltage<br>额定电压           | (3.3/5.0) V DC      |
| 2-4  | Pole count<br>磁性材料极对数           | 17 对共 34 极          |
| 2-5  | Output waveform type<br>输出波形类型  | AB 相方波              |
| 2-6  | With pull-up resistor<br>上拉电阻   | 3K3 $\Omega$        |
| 2-7  | Rotating Direction<br>旋转方向      | (CW/CCW)            |
| 2-8  | Operating Direction<br>固定方位     | 配合电机端子及后轴固定         |
| 2-9  | Grounding Polarity<br>接地极性      | NO polarity<br>无接地点 |
| 2-10 | Operating Voltage<br>电压使用范围     | (3.3~12.0) VDC      |
| 2-11 | Operating Temperature<br>工作温度范围 | 0℃~50℃              |
| 2-12 | Storage Temperature<br>存放温度范围   | 0℃~50℃              |
| 2-13 | 接线端子型号                          | XH2.54-4PIN         |

|   |                      |                          |
|---|----------------------|--------------------------|
| 型号/MODEL<br>CHP-42GP-775-5-ABHL 12V<br>820rpm | 规格书<br>SPECIFICATION | 页码/PAGE: 5/7             |
|   |                      | 版本/REVISION NO.: A/1.3   |
|   |                      | 编号/SERIAL NO.: CL-QR-323 |

3、ELECTRICAL CHARACTERISTICS: 电气性能


| NO. | Items/项目                                       | TEST CONDITIONS/测试条件   | SPECIFICATION/规格  |
|-----|--|--|---|
| 3-1 | Appearance<br>外观                               | Visual<br>目视   | No remarkable deformation or superficial defects to be observed by visual check.<br>无明显表面缺陷 |
| 3-2 | Dimension<br>外形尺寸                              | Measured by caliper<br>卡尺  | Refer to construction drawing.<br>符合图纸要求  |
| 3-3 | Mass<br>重量                                     | Measured by scale<br>天平  | Approximation: (630) g<br>约 (630) g   |
| 3-4 | Radial run-out<br>Deflection of Shaft<br>轴径向跳动 | 1.5mm from shaft top by dial gauge<br>轴针顶部对入 1.5mm 处<br> | $\leq (0.03) \text{ mm}$  |
| 3-5 | axial clearance<br>轴向间隙                        | Measured by dial gauge<br>百分表  | $(0.05) \sim (0.50) \text{ mm}$   |

|   |                         |  |   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
|---|-------------------------|--|---|-------------------|----------------|------------|---|------|-----|-----|---|------|-----|-----|---|------|--|-----|---|
| 型号/MODEL<br>CHP-42GP-775-5-ABHL 12V<br>820rpm |                         | 规格书<br>SPECIFICATION   | 页码/PAGE: 6/7  |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
|   |                         |  | 版本/REVISION NO.: A/1.3  |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
|   |                         |  | 编号/SERIAL NO.: CL-QR-323  |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 4、RELLABILITY SPECLAL IEST 可靠性、特殊试验           |                         |  |   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| NO.   | Items/项目                | Condition-Remark/条件-备注   | acceptance/判定基准   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 4-1   | LIFE TEST<br>寿命测试       | Motor test conditions are listed as below. Motor life is judged as end when either of the criteria described met.<br>如果满足下列项目中任何一项时，认为电机的寿命结束。<br>1、Rated load speed varies more than ±30% against the initial figure.<br>电机的负载转速、相对初始值超过±30%；<br>2、Rated load current varies move than +90%.against the initial figure.<br>电机的负载电流、相对初始值超过+90%；<br>3、Motor is confirmed to be unusable.<br>确认电机不可使用；<br>连续运转寿命≥800H             |   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 4-2   | Vibration test<br>耐振动试验 | Motor subjected to the sine wave of 2mm amplitude and 100/10Hz vibration in theX,Y and Z directions for 30 minutes each.<br>在 XYZ 方向承受振 2mm，振幅频率 100/10Hz 的正弦波振动各 30 分钟。   | ●Rated load speed varies within< ± 30% from the initial<br>额定负载转速变化：〈 ± 30%   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 4-3   | Shock test<br>跌落试验      | Smallest packing dropped on wooden block of 10mm thickness from 200mm height, once for each 6 faces of the packing.<br>把马达放进小包装中，在高度 200mm 处自然跌落在 10mm 厚的木板上。  | ●Rated load current varies within <± 30% from the initial<br>额定负载电流变化：〈 ± 30% |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 4-4   | Storage test<br>环境放置试验  | Measurement shall be made after the motor is returned in 20℃ for 24h.Each storage test is independent.<br>按下表各温度、湿度环境下放置试验，再在常温、常湿中放置 24hrs 后测定参数。 <table><tr><td></td><td>Temperature<br/>温度</td><td>Humidity<br/>湿度</td><td>Time<br/>时间</td></tr><tr><td>1</td><td>+85℃</td><td>30%</td><td>96h</td></tr><tr><td>2</td><td>+40℃</td><td>90%</td><td>96h</td></tr><tr><td>3</td><td>-30℃</td><td></td><td>96h</td></tr></table> |   | Temperature<br>温度 | Humidity<br>湿度 | Time<br>时间 | 1 | +85℃ | 30% | 96h | 2 | +40℃ | 90% | 96h | 3 | -30℃ |  | 96h | ●Rated load speed varies within ± 30% from the initial.额定负载转速相对初 始 值 变 化 ： 〈 30%<br>●Rated load current varies within ± 30%from the initial<br>额定负载电流相对初始值变化：〈30% |
|   | Temperature<br>温度       | Humidity<br>湿度   | Time<br>时间  |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 1   | +85℃                    | 30%  | 96h   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 2   | +40℃                    | 90%  | 96h   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |
| 3   | -30℃                    |  | 96h   |                   |                |            |   |      |     |     |   |      |     |     |   |      |  |     |   |

|   |                      |                          |
|---|----------------------|--------------------------|
| 型号/MODEL<br>CHP-42GP-775-5-ABHL 12V<br>820rpm | 规格书<br>SPECIFICATION | 页码/PAGE: 7/7             |
|   |                      | 版本/REVISION NO.:A/1.3    |
|   |                      | 编号/SERIAL NO.: CL-QR-323 |

Size

外形图 (Outline Drawing)




PS:4-M4螺纹的允许最大预紧扭力为8KG.CM

ps: The maximum allowable pretightening torque for 4-M4 thread is 8KG.GM



# Holzer Encoder Data



## Encoders Conflg

|                              |   |
|------------------------------|---|
| Type:                        | AB dual phase incremental encoder   |
| Pulse outputs of rotation:   | Basic pulse 17PPR x gear reduction ratio                                    |
| Holzer power supply voltage: | DC 3.3V / DC5.0   |
| Basic function:              | With the pull-up shaping resistor,the single-chip microcomputer can be used |
| Encoder Interface type:      | PH2.0-4PIN (Standard wiring)  |
| Motor power supply interface | VH3.96-2PIN(Standard wiring)  |
| Output signal type:          | Square wave AB phase  |
| Response frequency:          | 100KHz  |
| Basic pulse number:          | 17 PPR  |
| poles of magnetic ring:      | 34 poles(17 pairs of poles)   |