

Maximum Travel Speed

Max. Velocity (mm/s)

Type	Lead (mm)	Rail Length L (mm)													
		80	100	125	150	200	250	300	350	400	450	500	550	600	
LX20	1	190	190	-	190	190	-	-	-	-	-	-	-	-	
	5	-	694	-	694	694	694	633	-	-	-	-	-	-	
LX26	2	-	290	-	290	290	290	290	-	-	-	-	-	-	
	5	-	-	-	521	521	521	521	521	446	-	-	-	-	
LX30	5	-	-	410	410	410	410	410	410	410	410	370	300	250	
	10	-	-	-	830	830	830	830	830	830	830	740	600	500	
Type	Lead (mm)	Rail Length L (mm)													
		340	390	440	490	540	590								
LX45	10	550	550	550	550	550	550								
	20	1110	1110	1110	1110	1110	1110								

\*Values in the table are calculated on basis of critical speed and DN value of ball screws.  
Note that these are not guarantee data considering motor rotational speed, operating conditions, etc.

Accuracy Standards

Accuracy Standard Items	LX20		LX26		LX30 (L=400 or less)		LX30 (L=exceeding 400)		LX45	
	High Grade	Precision Grade	High Grade	Precision Grade	High Grade	Precision Grade	High Grade	Precision Grade	High Grade	Precision Grade
Positioning Accuracy (mm)	0.06	0.02	0.06	0.02	0.06	0.02	0.1	0.025	0.1	0.025
Positioning Repeatability (mm)	±0.005	±0.003	±0.005	±0.003	±0.005	±0.003	±0.005	±0.003	±0.005	±0.003
Backlash (mm)	0.01	0.003	0.01	0.003	0.02	0.003	0.02	0.003	0.02	0.003
Parallelism (mm)	0.025	0.01	0.025	0.01	0.025	0.01	0.035	0.015	0.035	0.015
Starting Torque (N · cm)	1.2		2		4		4		10	


Accuracy Standards

- Positioning Accuracy

Positioning is performed from a reference position incrementally in one direction, and measured.

Measurement values are the maximum difference between actual travel distance and commanded distance.

For standard values, please see "Accuracy Standards Table".




- Positioning Repeatability

Repeat positioning and measurement seven times at the same point in a specified direction.

1/2 of the maximum difference with "±" in front is defined as the measurement value.


For standard values, please see "Accuracy Standards Table".



- Backlash

Loads are applied to the block from the reference position, and then released. The difference between the reference position and returned value is the measurement value.

For standard values, please see "Accuracy Standards Table".




- Running Parallelism

A dial indicator is installed from the block to the reference surface. Measurements are taken while travelling.

The maximum difference taken by the measurement is the measurement value.

For standard values, please see "Accuracy Standards Table".



Maintenance

- Routine Inspections:

Recommended inspection frequency is once per 3 to 6 months.  
Please check for proper lubrication conditions, clean-up and grease refill.  
Check on mounting screws for looseness.

- Lubrication:

The recommended lubricants are shown as below.  
LX20, LX26 and LX30 Series => Showa Shell Sekiyu-made Alvania Grease S No.2  
LX45 Series => Showa Shell Sekiyu-made Cartridge Grease EP2  
Low Particle Generation Type => NSK LG2  
Recommended greasing cycle is per 6 months or 1,000km under normal operating conditions.  
\* Lubrication intervals, however, depend on usage conditions and environments.

Cautions for Operating Environments:

Ensure that it is used at an ambient temperature of 50°C or below, It is recommended to provide mechanical stoppers to prevent overrun.

- Allowable Rotational Speed

Size-specific allowable rotational speed is indicated below.

Part Number	Lead	Rail Length	Allowable Rotational Speed (min <sup>-1</sup> )
LX20	1	80~300	6000
	5		
LX26	2	100~400	6000
	5		
LX45	10	340~590	3300
	20		

Part Number	Lead	Rail Length	Allowable Rotational Speed (min <sup>-1</sup> )
LX30	5	150~450	4,920
		500	4,440
		550	3,600
	10	600	3,000
		150~450	4,980
		500	4,440
		550	3,600
		600	3,000


About Single-axis Actuator LX Low Particle Grease

The products are shipped with low particle generation grease applied for clean room environments.  
LG2 (Made by NSK Ltd.) generates less particles and exhibits excellent corrosion resistance.  
For part number selections, please see each product page.

Low Particulate Generation Grease Performance Table


Items	Conditions	Unit	Measurement Method	LG2 (Made by NSK Ltd.)
Thickener	-	-	-	Lithium Type
Base Oil	-	-	-	Mineral Oil + Synthetic Hydrocarbon Oil
Base Oil Kinetic Viscosity	40°C	mm <sup>2</sup> /s	JIS K2220 5.19	30
Worked Penetration	-	-	JIS K2220 5.3	207
Dropping Point	-	°C	JIS K2220 5.4	200
Evaporation	99°C x 22hr	wt%	-	1.40%
Oil Separation	100°C x 24hr	wt%	JIS K2220 5.14	0.80%
Operating Temp.	In Air	°C	-	-10~80

Particulate Generation Comparison



Measuring Time	1H	2H	3H	4H	5H	6H	7H	8H	9H
LX (Low Particulate Generation Grease)	8	12	4	7	2	1	1	2	3
LX (Standard)	8	8	12	13	15	16	14	20	18

Particle Generation Test Evaluation Equipment Outline



<Evaluation Conditions>

Clean Room Class 100 (in a clean room)  
Room Temperature 24°C±2°C Humidity 45%±5%  
(Particle Counter Name)  
Hand-held Particle Counter KR-12A (Rion Co., Ltd.)  
Tested Actuator: LX2001-B1-A2040-200  
Motor Speed: 3000rpm

Clean Room Class 100/ISO Class 5  
The measurement results meet the conditions above.  
(\* These are not guaranteed values but reference values.  
Values considerably varies depending on operating environment)